


Deep Socket

2230M



- DIN 3124, ISO 2725-1



KT NO.	mm	D1 mm	D2 mm	ℓ mm	L mm	g	kg	mm
223004M	4	6.8	11.8	6	50	20	20	320
223045M	4.5	7.4	11.8	7	50	20	20	320
223005M	5	8.0	11.8	7	50	20	20	320
223055M	5.5	8.7	11.8	9	50	20	20	320
223006M	6	9.2	11.8	9	50	21	20	320
223007M	7	10.3	11.8	15	50	22	20	320
223008M	8	11.8	11.8	15	50	25	20	320
223009M	9	13.0	13.0	15	50	28	15	240
223010M	10	14.5	14.5	15	50	36	15	240
223011M	11	15.8	15.8	21	50	41	15	240
223012M	12	16.8	16.8	21	50	47	15	240
223013M	13	17.8	17.8	21	50	49	15	240
223014M	14	19.8	19.8	21	50	66	15	240


Double Square Socket

2310M

2310S



- Metric-DIN 3120
- Inch-ANSI / ASME B107.1




KT NO.	mm	D1 mm	D2 mm	ℓ mm	L mm	g	kg	mm
231008M	8	13.8	13.0	9	24	16	12	360
231010M	10	16.8	15.4	9	24	22	12	360
KT NO.	inch	D1 mm	D2 mm	ℓ mm	L mm	g	kg	mm
231010S	5/16	13.8	13.0	9	24	15	12	360
231012S	3/8	16.8	15.4	9	24	24	12	360

Star Socket

2375M



- DIN 3120




KT NO.	Size	D1 mm	D2 mm	ℓ mm	L mm	g	kg	mm
237504M	E4	6.0	11.8	3.6	24	9	20	600
237505M	E5	7.0	11.8	4.0	24	10	20	600
237506M	E6	8.0	11.8	6.0	24	10	20	600
237507M	E7	8.5	11.8	7.0	24	11	20	600
237508M	E8	9.8	11.8	8.0	24	11	20	600
237510M	E10	11.8	11.8	9.0	24	13	20	600

Star Socket

2275M



- DIN 3120



KT NO.	Size	D1 mm	D2 mm	ℓ mm	L mm	g	kg	mm
227504M	E4	6.0	11.8	3.6	50	21	20	320
227505M	E5	7.0	11.8	4.0	50	22	20	320
227506M	E6	8.0	11.8	6.0	50	24	20	320
227507M	E7	8.5	11.8	7.0	50	24	20	320
227508M	E8	9.8	11.8	8.0	50	26	20	320

Bit Socket




In order to get normal life of bit socket, always use within limited torque to bit.

2011X



- Phillips head
- DIN ISO 8764-1




KT NO.	No.	L mm	g	kg
201101X	PH1	25	9	20 / 600
201102X	PH2	25	9	20 / 600
201103X	PH3	25	10	20 / 600
201104X	PH4	25	12	20 / 600

2012X



- Slotted head
- DIN ISO 2380-1




KT NO.	Tip width mm	Tip thickness mm	L mm	g	kg
201235X	3.5	0.6	25	8	20 / 600
201255X	5.5	1.0	25	9	20 / 600
201208X	8	1.2	25	10	20 / 600

2015X



- Hexagon head
- DIN ISO 2380-1



KT NO.	mm	L mm	g	kg
201503MX	H3	25	8	20 / 600
201504MX	H4	25	9	20 / 600
201505MX	H5	25	10	20 / 600
201506MX	H6	25	10	20 / 600
201508MX	H8	25	13	20 / 600
201510MX	H10	25	15	20 / 600
201506SX	3/16	25	9	20 / 600
201508SX	1/4	25	10	20 / 600