

Impact Accessory

3864P

3/8"

- Adapter
- Convert to 1/2" drive
- DIN 3121



KT NO.	Spec.	D mm		
3864P	3/8"F x 1/2"M	20.8	53	24 / 384

3147

3/8"

- Bit holder



KT NO.	Size	L mm		
314708S	1/4"	40	41	12 / 420
314710S	5/16"	40	43	12 / 420
314710M	10mm	40	42	12 / 420

3260P

3/8"

- Extension bar
- DIN 3121




KT NO.	Overall length inch	mm		
3260-03P	3	75	98	6 / 120
3260-04P	4	100	121	8 / 160
3260-05P	5	125	147	8 / 144
3260-06P	6	150	169	5 / 100
3260-08P	8	200	217	6 / 72
3260-10P	10	250	264	6 / 54

3796P

3/8"

- Universal joint
- DIN 3121



KT NO.	Overall length inch	mm	D mm		
3796P	2	50	22	87	10 / 200

90608

- Locking pin
- Chrome vanadium steel
- DIN 3129

90609

3/8"



KT NO.	Desp.	Ø	d / ℓ	Applied to socket sizes
90608	pin	2.5	14	3535M (6~12 mm) 3535S (1/4~1/2 inch) 3435M (6~12 mm) 3435S (1/4~1/2 inch) 3055M (4~12 mm) 3055S (3/16~1/2 inch) 3065M (4~10 mm) 3053 (T10~T15) 3575M (E5~E14) 3053.3055.3065.3147.3862.3864
90609	pin	2.5	16	3535M (13~19 mm) 3535S (9/16~3/4 inch) 3435M (13~24 mm) 3435S (9/16~7/8 inch) 3260.3796

Impact Bit Socket Set

3406MP

3/8"

- For hexagon head screw
- 55mmL

6
PC.



Metal case size (mm) :
203 x 79 x 41 (0.023 cuft)

Contents



0.72



1 / 20



3055M

H4, H5, H6, H8, H10, H12

3419PP

3/8"

- For torx internal head
- 55mmL

9
PC.



Metal case size (mm) :
203 x 79 x 41 (0.023 cuft)

Contents



0.62



1 / 20



3053

T10, T15, T20, T25, T27, T30, T40,
T45, T50

Standard Impact Socket


KT No. & D1



4530M

1/2"

- DIN 3129, ISO 2725-2



KT NO.	Ø mm	D1 mm	D2 mm	ℓ mm	L mm		
453008M	8	15.0	25	7	38	65	10 / 200
453009M	9	16.3	25	7	38	68	10 / 200
453010M	10	17.6	25	8	38	68	10 / 200
453011M	11	18.8	25	8	38	69	10 / 200
453012M	12	20.0	25	9	38	73	10 / 200
453013M	13	21.2	25	10	38	71	10 / 200
453014M	14	22.5	25	10	38	78	10 / 200
453015M	15	23.8	30	11	38	111	10 / 160
453016M	16	25.0	30	11	38	118	10 / 160
453017M	17	26.2	30	12	38	116	10 / 160
453018M	18	27.5	30	13	38	115	10 / 160
453019M	19	28.8	30	13	38	114	10 / 160
453020M	20	29.5	30	13	38	117	10 / 160
453021M	21	30.0	30	14	40	121	8 / 160
453022M	22	32.4	30	14	40	129	8 / 160
453023M	23	33.2	30	15	40	130	8 / 160
453024M	24	34.4	30	15	42	147	6 / 120
453025M	25	36.0	30	15	42	164	6 / 120
453026M	26	37.0	30	15	42	168	6 / 120
453027M	27	38.0	30	16	44	170	6 / 120
453028M	28	41.0	30	16	44	205	6 / 120
453029M	29	41.0	30	17	44	184	6 / 120
453030M	30	42.0	30.5	17	44	197	6 / 120
453032M	32	46.0	30	19	44	226	6 / 120
453033M	33	46.0	30	19	46	246	6 / 96
453034M	34	46.0	30	20	46	217	6 / 96
453036M	36	47.0	30	20	46	214	6 / 96
453038M	38	50.0	30	21	50	279	6 / 60
453041M	41	56.0	30	22	52	402	6 / 60